



Cable type

PANZERFLEX-EL 3,6 ÷ 12/20 kV
(N)TSCGEWÖU - H.V. reeling cable 6 to 20 kV

Main application

Flexible H.V. reeling power cables for use on connecting movable parts of machine tools and any material handling equipment (i.e. Stacker/reclaimer, ship to shore crane, container crane, excavators, also suitable for festoon system). Perfectly suitable for any energy supply on cable reels systems associated from high to extreme mechanical stresses, frequent bending/torsional operation and fast movement with strong acceleration

Construction

Conductor:	Tinned copper conductor, flexible cl.5 IEC 60228 Specially designed for mobile application
Insulation:	Micro filtered HEPR rubber compound better than 3GI3 New specially developed compound with improved electrical and mechanical characteristics
Cores identification:	Main cores: natural colour with black semiconductive layer Splitted earth cores: identified by position and covered with special black semiconductive compound
Field control:	- Conductor screen: semiconductive layer - Cnsulation screen: semiconductive layer of special compound Applied with insulation
Laying-up:	Short lay length for better flexibility and mechanical characteristics ≤ 8 times the laying-up cores diameter, three cores design with protective earth cores split in 3 interstitial areas
Separation (if any):	Tape(s)
Inner sheath:	Polychloroprene rubber based compound Special developed with improved mechanical characteristics
Antitwisting protection:	Textile braid of synthetic yarns Firmly bonded between inner and outer sheath
Outer sheath:	Red polychloroprene rubber compound UV resistant, oil and chemical resistant better then 5GM3 compound
Marking:	PALAZZO - PANZERFLEX-EL <i>rated voltage nc x cross section year of manufacturing</i>

Parameters

Electrical	Rated voltage	U ₀ /U = 3,6/6 kV to 12/20 kV*
	Maximum permissible operating voltage in AC systems	U _m = 7,2 kV to 24 kV
	AC test voltage over 5 minutes	11 kV to 29 kV according to VDE 0250 part 813
	Current Carrying Capacity	According to DIN VDE 0298 part 4
EMC	simmetrical design + narrow production tolerances	very low interference
Thermal	Fully flexible operation	- 30 °C
	Fixed installation	- 40 °C
	Maximum permissible operating temperature of the conductor	90 °C
	Short-circuit temperature of the conductor	250 °C
Mechanical	Tensile load	Up to 20 N/mm ²
	Minimum bending radii	According to DIN VDE 0298 part 3
	Reeling operation	No restriction. Consult the manufacturer if speed exceeds 180 m/min
	Festoon systems	Up to 120 m/min
Chemical	Resistance to oil	According to VDE / IEC standard
	Weather resistance	Unrestricted use outdoor and indoor, UV resistant, moisture resistant.







Table 1: PANZERFLEX-EL 3.6 ÷ 12/20 kV (N)TSCGEWÖU

N. of cores and nominal section n-mm ² +n-nm ² /3	Main conductor		Protective earth cond. nom. diam. mm	Overall diameter		Net weight approx. kg/km	Maximum permissible tensile force N	Current carrying capacity at 30 °C				Short circuit current 80 ° to 200 °C kA
	D.C. resist. at 20 °C Ohm/km	nom. diam. mm		min.	value mm			Laid straight A	Spiral or 1 layer A	2 layer A	3 layer A	
3,6/6 kV												
3x25+3x25/3	0,795	6,6	4,0	39,4	42,4	2580	1500	131	105	80	64	3,2
3x35+3x25/3	0,565	8,0	4,0	42,0	45,0	3110	2100	162	130	99	79	4,5
3x50+3x25/3	0,393	9,3	4,0	44,8	47,8	3660	3000	202	162	123	99	6,4
3x70+3x35/3	0,277	11,2	4,9	48,4	52,4	4620	4200	250	200	153	123	9,0
3x95+3x50/3	0,210	13,0	5,4	53,5	57,5	5740	5700	301	241	184	147	12,2
3x120+3x70/3	0,164	15,0	6,6	57,8	61,8	7140	7200	352	282	215	172	15,4
3x150+3x70/3	0,132	16,9	6,6	63,3	67,3	8400	9000	404	323	246	198	19,2
3x185+3x95/3	0,108	18,3	8,0	66,5	70,5	9870	11100	461	369	281	226	23,7
3x240+3x120/3	0,0817	20,5	9,3	75,3	79,3	12790	14400	540	432	329	265	30,7
6/10 kV												
3x25+3x25/3	0,795	6,6	4,0	41,1	44,1	2740	1500	131	105	80	64	3,2
3x35+3x25/3	0,565	8,0	4,0	43,8	46,8	3280	2100	162	130	99	79	4,5
3x50+3x25/3	0,393	9,3	4,0	46,6	49,6	3840	3000	202	162	123	99	6,4
3x70+3x35/3	0,277	11,2	4,9	51,4	55,4	4960	4200	250	200	153	123	9,0
3x95+3x50/3	0,210	13,0	5,4	55,2	59,2	5960	5700	301	241	184	147	12,2
3x120+3x70/3	0,164	15,0	6,6	59,5	63,5	7370	7200	352	282	215	172	15,4
3x150+3x70/3	0,132	16,9	6,6	65,2	69,2	8650	9000	404	323	246	198	19,2
3x185+3x95/3	0,108	18,3	8,0	68,3	72,3	10130	11100	461	369	281	226	23,7
3x240+3x120/3	0,0817	20,5	9,3	76,5	80,5	13010	14400	540	432	329	265	30,7
8,7/15 kV												
3x25+3x25/3	0,795	6,6	4,0	44,5	47,5	3080	1500	139	111	85	68	3,2
3x35+3x25/3	0,565	8,0	4,0	47,2	50,2	3640	2100	172	138	105	84	4,5
3x50+3x25/3	0,393	9,3	4,0	50,7	54,7	4360	3000	215	172	131	105	6,4
3x70+3x35/3	0,277	11,2	4,9	55,0	59,0	5380	4200	265	212	162	130	9,0
3x95+3x50/3	0,210	13,0	5,4	58,7	62,7	6430	5700	319	255	195	156	12,2
3x120+3x70/3	0,164	15,0	6,6	62,8	66,8	7850	7200	371	297	226	182	15,4
3x150+3x70/3	0,132	16,9	6,6	68,7	72,7	9170	9000	428	342	261	210	19,2
3x185+3x95/3	0,108	18,3	8,0	73,5	77,5	10990	11100	488	390	298	239	23,7
3x240+3x120/3	0,0817	20,5	9,3	79,1	83,1	13460	14400	574	459	350	281	30,7
12/20 kV												
3x25+3x25/3	0,795	6,6	4,0	48,8	52,8	3580	1500	139	111	85	68	3,2
3x35+3x25/3	0,565	8,0	4,0	52,7	56,7	4320	2100	172	138	105	84	4,5
3x50+3x25/3	0,393	9,3	4,0	55,5	59,5	4940	3000	215	172	131	105	6,4
3x70+3x35/3	0,277	11,2	4,9	59,6	63,6	6020	4200	265	212	162	130	9,0
3x95+3x50/3	0,210	13,0	5,4	65,0	69,0	7340	5700	319	255	195	156	12,2
3x120+3x70/3	0,164	15,0	6,6	69,3	73,3	8820	7200	371	297	226	182	15,4
3x150+3x70/3	0,132	16,9	6,6	75,2	79,2	10260	9000	428	342	261	210	19,2
3x185+3x95/3	0,108	18,3	8,0	77,8	82,8	11770	11100	488	390	298	239	23,7

18/30 kV available on request