

# Main features summary

	MAX WORKING SPEED	RATED VOLTAGE	TEST VOLTAGE	WORKING TEMP. ON THE CONDUCTOR	SHORT CIRCUIT TEMP.	OIL RESISTANCE	OZONE RESISTANCE	UV RESISTANCE	BURNING BEHAVIOR	MONOSPIRAL DRUM	MULTISPIRAL DRUM	CYLINDRICAL DRUM	VERTICAL DRUM	SPREADER BASKET	MOTORIZED SPREADER	FESTOON	SYSTEM WITH CABLE TENDERS	GUIDE PULLEY SYSTEMS	CARRIER CHAINS
	m/min	V-kV	kV	°C	°C														
UTVFLEX® / UTVFLEX® - S	120	0,6/1	4	90	250	✓	✓	✓	✓	✗	✗	✗				✗			✗
UTVFLEX® - VS	180	0,6/1	4	90	250	✓	✓	✓	✓	✗	✗	✓	✓		✓		✓	✓	
UTVFLEX® - PUR HF	180	0,6/1	4	90	250	✓	✓		✓	✗	✗	✓	✓				✓	✓	
UTVFLEX® - SPR	240	0,6/1	4	90	200	✓	✓	✓	✓		✗	✓	✓		✓		✗	✗	
UTVFLEX® BASKET	160	0,6/1	2	70*	150**	✓	✓		✓					✓					
UTVFLEX® FESTOON / FESTOON FO	240	0,6/1	4	90	250	✓	✓	✓	✓							✓			
UTVFLEX® - R MT / R-MT FO	120	3,6/6 6/10 8,7/15 12/20 11/17/24/29	4	90	250	✓	✓	✓	✓	✗	✗	✗							✗
UTVFLEX® - RF/MT FO	240	3,6/6 6/10 8,7/15 12/20 11/17/24/29	4	90	250	✓	✓	✓	✓	✗	✗	✗							✗

ON REQUEST AVAILABLE:  
\* 90°C UTVFLEX® BASKET  
\*\* 250°C UTVFLEX® BASKET

Main application Suitable